






# Tracking of the Ions for the CeC experiment with Cooling Force Depending on Longitudinal Location of the Ion

G. Wang

# What has been done differently...

## Fitting-> linear interpolation










Transverse core (linear interpolation)?

---




# Energy kick from Ideal beam vs Simulated beam




Using energy kick from the best slice, i.e. slice # 26 and assume the kick applies for 15 ps of electrons






Using kicks from slice 26, 28 and 29 with each slice has 5 ps of duration



# Using kicks from 6 slices with 1.2 ps of duration for each slice



Electron bunch




# Summary

- The tracking code is updated so that the energy kick calculated from SPACE simulation is directly used with linear interpolation applied between data points.
- It has been implemented into the tracking code that ions sitting at different longitudinal slice of the electron bunch see different form of the cooling force. The cooling force for each slice of electrons depends on the local properties of the electrons and is provided by SPACE simulation.
- According to the simulation, cooling effect is very weak with the electron beam as obtained from the previous beam dynamic simulation, i.e. 7% of peak current increases over 40 minutes, even without energy jitter and other adverse effects.
- We need to improve electron beam quality so that we have 15 ps of duration with energy kick comparable to that of the best slice of the previous simulated electrons, i.e. slice 26.




# Updates with new solenoid settings (comparison of cooling kicks)

Best slice






'Worst' slice



# Updates with new solenoid settings

Electron bunch



# Latest SPACE simulation results for e beam size (old electron distribution)


$$\sigma_{ion} = \sqrt{\frac{2.5 \mu m \cdot 7.5 m}{28.5}} = 0.8 mm$$

(\*The beta function at kicker varies from 8.5 m to 14.3 m, corresponding to average ion beam size of 1 mm. To be corrected...)

- Poor spatial overlapping of the electrons with the ions can reduce the cooling effects.
- In order to properly study the effects, one need to obtain the dependance of the cooling energy kick on the transverse offset of the ion.
- As a start, I assumed Gaussian dependance in the simulation for now.

$$dE(z) \rightarrow dE(z) \exp\left(-\frac{x^2}{2\sigma_x^2} - \frac{y^2}{2\sigma_y^2}\right)$$



$\sigma_{x,y}$ : rms width of the slice of electrons that the ion is overlapping with




# Influences due to finite transverse size of the electron bunch

- Assuming the energy kick in CeC section has Gaussian dependance on the transverse offset of the ion with the R.M.S. width given by the R.M.S. size of the electron slice.

As a test, start from the ideal case...






Then use the latest SPACE simulated energy kicks for 7 slices



# Results for Solenoids Matched to e Slice with the Maximal Current

Electron bunch



# Summary on influences from transverse dependance of the cooling force

- If we assume Gaussian dependance of the cooling force on the transverse offset of the ion with the rms width given by that of the electron slices, the observable of the cooling effects, i.e. the enhancement of the peak current of the ion bunch w.r.t. the witness bunch, reduces by a factor of  $\sim 4$  compared with the case when these effects are ignored.
- The significant reduction is related to the fact that the electron bunch is smaller than the ion bunch in the transverse plane (0.2-0.5 mm for the electrons vs 0.8 mm (should be 1 mm) for the ions). If we can make the transverse size of the electrons the same as that of the ions without reducing the cooling force at the center of the electron bunch, the cooling effect can be improved by a factor of 2.

## Next step...

- Implement a better model for cooling dependance on the transverse offset: disk model and then SPACE simulation.



# Disc model

$$\rho(r, \theta, z) = \rho_0 f_{//}(z) f_{\perp}(r)$$

$$\frac{1}{r} \left[ \frac{\partial}{\partial r} \left( r \frac{\partial}{\partial r} \varphi(r, z) \right) \right] + \frac{\partial^2}{\partial z^2} \varphi(r, z) = \frac{\rho_0}{\epsilon_0} f_{//}(z) f_{\perp}(r)$$



$$\frac{\partial^2}{\partial r^2} \phi + \frac{1}{r} \frac{\partial}{\partial r} \phi - k^2 \phi = f(r)$$

$$f(r) = \frac{\rho_0}{\epsilon_0} f_{\perp}(r) \int_{-\infty}^{\infty} e^{-ikz} f_{//}(z) dz = \frac{\rho_0}{\epsilon_0} f_{\perp}(r) \tilde{f}_{//}(k)$$



Flat disc

$$f(r) = \frac{\rho_0}{\epsilon_0} \tilde{f}_{//}(k) \frac{1}{\pi a^2} H(a - r)$$

$$E_z(r) = -ik \frac{\rho_0}{\pi \epsilon_0} \tilde{f}_{//}(k) \left[ I_0(kr) \int_{r/a}^1 \eta H(1 - \eta) K_0(ka \cdot \eta) d\eta + K_0(kr) \int_0^{r/a} \eta H(1 - \eta) I_0(ka \cdot \eta) d\eta \right]$$




# Dependance of Cooling Force on Transverse Offset: Disc Model (Flat Disc)

$$E_z(r) = -ik \frac{\rho_0}{\pi \epsilon_0} \tilde{f}_{//}(k) \left[ I_0(kr) \int_{r/a}^1 \eta H(1-\eta) K_0(ka \cdot \eta) d\eta + K_0(kr) \int_0^{r/a} \eta H(1-\eta) I_0(ka \cdot \eta) d\eta \right]$$



# Dependance of cooling force on transverse offset: step function

Electron bunch



# Disc model, Gauss disk

$$\rho(r, \theta, z) = \rho_0 f_{//}(z) f_{\perp}(r)$$

$$\frac{1}{r} \left[ \frac{\partial}{\partial r} \left( r \frac{\partial}{\partial r} \phi(r, z) \right) \right] + \frac{\partial^2}{\partial z^2} \phi(r, z) = \frac{\rho_0}{\epsilon_0} f_{//}(z) f_{\perp}(r)$$



$$\frac{\partial^2}{\partial r^2} \phi + \frac{1}{r} \frac{\partial}{\partial r} \phi - k^2 \phi = f(r)$$



$$f(r) = \frac{\rho_0}{\epsilon_0} f_{\perp}(r) \int_{-\infty}^{\infty} e^{-ikz} f_{//}(z) dz = \frac{\rho_0}{\epsilon_0} f_{\perp}(r) \tilde{f}_{//}(k)$$

$$f(r) = \frac{\rho_0}{\epsilon_0} \tilde{f}_{//}(k) \frac{1}{2\pi\sigma_r^2} \exp\left(-\frac{r^2}{2\sigma_r^2}\right) \quad \sigma_x = \sigma_y = \sigma_r$$


$$\begin{aligned} \tilde{E}_z(r, k) &= -ik \frac{\rho_0 \tilde{f}_{//}(k)}{2\pi\epsilon_0\sigma_r^2} \left\{ I_0(kr) \int_{\infty}^r \xi K_0(k\xi) e^{-\frac{\xi^2}{2\sigma_r^2}} d\xi - K_0(kr) \int_0^r \xi I_0(k\xi) e^{-\frac{\xi^2}{2\sigma_r^2}} d\xi \right\} & \bar{r} &\equiv \frac{r}{2\sigma_r} \\ &= -ik \frac{2\rho_0 \tilde{f}_{//}(k)}{\pi\epsilon_0} \left\{ I_0(\bar{k}\bar{r}) \int_{\infty}^{\bar{r}} \bar{\xi} K_0(\bar{k}\bar{\xi}) e^{-2\bar{\xi}^2} d\bar{\xi} - K_0(\bar{k}\bar{r}) \int_0^{\bar{r}} \bar{\xi} I_0(\bar{k}\bar{\xi}) e^{-2\bar{\xi}^2} d\bar{\xi} \right\} & \bar{k} &\equiv 2k\sigma_r \end{aligned}$$

# Disc Model, Gauss disk



To compare Gaussian disk with flat disk, we take  $\sigma_r = a/2$  with  $a$  being the radius of a flat disk. By doing this, the two disk models have the same rms transverse spatial size.



# Simulated dependance for time-varying transverse profile







Going through an additional waist can reduce the integrated energy kick significantly except for the ions with  $r < 0.25\sigma_r$ .




# All simulated slices

Amplitude of the energy kick,  
i.e.  $(dE_{\text{MAX}} - dE_{\text{MIN}})/(2E_0)$



Averaged over the transverse profile of the ion bunch with RMS size of 1mm






$$E_{i_{slice}} = 2\pi \sum_{j=1}^{10} \frac{E_{i_{slice}}(r_j) + E_{i_{slice}}(r_{j+1})}{2} \frac{1}{2\pi\sigma_{ion}^2} \exp\left[-\frac{1}{2\sigma_{ion}^2} \left(\frac{r_j + r_{j+1}}{2}\right)^2\right] \cdot \left(\frac{r_j + r_{j+1}}{2}\right) \cdot \Delta r \quad \Delta r = r_{j+1} - r_j$$








# What has been done differently in the ion tracking code...

Electron bunch



# Results from ion tracking with 2D interpolation

Electron bunch





# NEXT STEPS



- Continue optimizing electron bunch for both high gain at bunch center and better uniformity over the whole bunch; If possible, try to increase beta function at modulator and kicker (Plasma phase advance at modulator is 1.1 rad with rms beam size of 1mm and 50A of peak current). (Yichao and Jun)
- Investigate how the cooling performance varies with the emittance of the ion bunch and explore possibilities of reduce transverse emittance of the RHIC ion beam. (Gang)
- Introduce transverse offset of the ion at both the modulator and the kicker section. Obtain cooling wakes for ions with various transverse offset through the cooling section (Jun). Investigate how the cooling performance is affected by the transverse offset (Gang).
- Explore possibilities of unsymmetric IR2 at the modulator and kicker to optimize cooling performance. (Gang, Jun and Yichao)

# Influence of $\beta_{ion}$ at the kicker section on the cooling performance



## Wakes from slice #45 with 13.2 ps of duration





Cooling longer with 2.85 m of beta function  
(Incorrect, 11.4 meters of beta function was used for 85 min results)



# Check convergence with tscale




# Cooling longer with 2.85 m of beta function (corrected)





# Cooling with 2.85 m of beta function

## Evolution of RMS bunch length







# Influence of reducing Ion beam beta function by a factor of 4 at the cooling section





# RMS bunch length



# Add energy jitter (Gaussian jitter)




# Comparison of current profile between two set-up




# Comparison of cooling force

Previous set up in 2022/11





(a) Old 45

Latest set up in 2023/1





(b) New 15


# Cooling performance comparison 2022.11 vs 2023. 1




# Comparison of cooling forces (Best slice in 2022.11 vs 50A, 1.5 $\mu$ m)



(a) Old 45




# Results for 50A, 1.5 $\mu\text{m}$ , 15 ps uniform beam








Latest set up with 50 A and 1.5 $\mu$ m emittance  
(setup 041124)




# Cooling wakes

Relative energy deviation of slices



# Correlation between shift of cooling wake and energy deviation of the slices





$$\Delta z_{field} = \tilde{R}_{56} \delta_{slice}$$



The coefficient,  $\tilde{R}_{56}$ , obtained from the fitting is 2.06 cm.



# Tracking results with 18 slices

- The new setup does not give much improvement compared with the previous setup, simulated on 11/30/2022.
- If I sum up on-axis field ( $x=0$ ) for all 18 slices, the summed field for the latest setup is about a factor of 2 less than the sum of 11 slices from setup 113022 and a factor of 3~4 less than the uniform field with 15 ps, 1.5um and 50A.
- The transverse dependance of the latest setup, 041124 is improved compared with setup 113022 and that's likely why the cooling performance is slightly better than what obtained from setup 113022.



# Comparison of transverse averaged wake amplitude between set up 113022 and 041124





# What about the $2e-4$ energy jitter tolerance?

- Energy jitter of  $2e-4$  reduces the observable, i.e. peak current difference between cooled and uncooled bunch, by a factor of 2;
- The studies was done for uniform wake and different ion beam parameters (assumed before 2022), i.e. before we start to consider reduction of cooling due to variation from slice to slice. The cooling effects was stronger and hence reduction of a factor of 2 still tolerable;
- I will repeat the energy jitter studies for the current parameters.

Table 1: Parameters of the Electron Bunch

Energy, $\gamma$	28.5
Peak current, A	75
Full bunch length, ps	15
Energy spread R.M.S.	$2 \times 10^{-4}$
Norm. emittance, R.M.S., mm.mrad	1.5

Table 2: Parameters of the Ion Bunch

Energy, $\gamma$	28.5
Bunch intensity	$8.4 \times 10^8$
Bunch length, R.M.S., ns	3.5
Energy spread R.M.S.	$1.2 \times 10^{-3}$
Longi. emittance, R.M.S., eV.s/u	0.36
Norm. emittance, R.M.S., mm.mrad	2.5
$\beta^*$ at cooling section, m	5
RF voltage (28 MHz cavities), KV	400

# Summary for setup 041124

- The amplitude of the cooling field and the transverse flatness seems better than previous setup.
- However, the alignment of cooling field from slices needs to be improved, i.e. only 6-7 slices are more or less aligned.
- The mis-alignment is caused by energy deviation of the electrons' slices. We need to reduce the correlated energy variation of the electron beam.

# PCA dependance on emittance




FIG. 3. 3D plot of the absolute value of the growth rate per cell:  $\lambda = \max(|\text{Re}\lambda_1|, |\text{Re}\lambda_2|)$ . There is a clearly identifiable ridge along the  $k_\beta \cong 3 \cdot (k_{sc} - 1.2)$  line, where growth rates peak.

$$\frac{d^2 \hat{a}}{d\hat{s}^2} - k_{sc}^2 \hat{a}^{-1} - k_\beta^2 \hat{a}^{-3} = 0;$$

$$\frac{d^2}{d\hat{s}^2} \tilde{g}_k + 2 \frac{k_{sc}^2}{\hat{a}(\hat{s})^2} \cdot \tilde{g}_k = 0; \quad \hat{a} = \frac{a}{a_o} \geq 1;$$

$$\hat{s} = \frac{s}{l}; \quad \hat{s} \in \{-1, 1\},$$

$$k_{sc} = \sqrt{\frac{2}{\beta_o^3 \gamma_o^3} \frac{I_o}{I_A} \frac{l^2}{a_o^2}}; \quad k_\beta = \frac{\epsilon l}{a_o^2}.$$

PLASMA-CASCADE INSTABILITY






FIG. 4. Contour plots of the absolute value of the cell's growth rate:  $\lambda = \max(|\text{Re}\lambda_1|, |\text{Re}\lambda_2|)$ . The purple area highlighted by white lines shows the areas of the stable oscillations  $|\lambda_{1,2}| = 1$ . Outside of these areas, the oscillations grow exponentially.

PHYS. REV. ACCEL. BEAMS **24**, 014402 (2021)



# Check IBS routine with measurement in FY 21

7/4/2021 20:44



I can't find any IPM emittance measurements during CeC dedicated time in Run 21, but the measurement for regular RHC store looks smaller than 15 mm.mrad



# Ion beam size

$$\beta(s) = \beta^* + \frac{s^2}{\beta^*}$$

$$s_1 = 4m$$

$$s_2 = 7m$$

$$\bar{\beta} = \beta^* + \frac{s_1^2 + s_2^2}{2\beta^*} \geq 2\sqrt{\beta^* \frac{s_1^2 + s_2^2}{2\beta^*}} = \sqrt{2(s_1^2 + s_2^2)}$$

The minimal average beta happens at  $\beta^* = \sqrt{\frac{s_1^2 + s_2^2}{2}}$ .